

Model	AMWP 11.5-8100
S.W.L	200kg
Max. Occupants	2
Max. Working Height	11.20m
Max. Platform Height	9.20m
Max. Horizontal Reach	3.00m
Up and Over Height	7.89m
Overall Length A	2.53m
Overall Width B	1.00m
Overall Height C	1.99m
Platform Size(Length/Width)	0.62m×0.87m
Ground Clearance(Stowed)	0.06m
Ground Clearance(Raised)	0.019m
Wheelbase D	1.22m
Turning Radius(Inside/Outside)	0.23/1.65m
Turret Rotation	345°
Jib Movement	+70°/-60°
Drive Motor	24V/1.5kW
Lifting Motor	24V/3kW
Travel Speed(Stowed)	4.5km/h
Travel Speed(Raised)	0.5km/h
Up/Down Speed	70/50sec
Batteries	24V/240Ah
Integrated Charger	24V/30A
Gradeability	25%
Max. Working Slope	2.5°
Tyres	Φ381×127mm
Weight	2950kg

Standard Equipment

Proportional Controls
Automatic Pothole Protection
Self-lock Gate On Platform
Drivable At Full Height
Charger Protection
Non Marking Tyre
2WD
Automatic Brake System
Emergency Lowering System
Flashing Beacon
Emergency Stop Button
Cylinder Holding Valve
Onboard Diagnostic System
Tilt Sensor With Alarm

345°Turret Rotation
All Motion Alarm
Horn
Hour Meter
Swing Out Components Cover
Platform Horizontal Outreach
Overload Sensor With Alarm

Options

Platform Work Lights
AC Power To Platform
Airline To Platform





Model	AMWP 11.5-8100
S.W.L	200kg
Max. Occupants	2
Max. Working Height	11.20m
Max. Platform Height	9.20m
Max. Horizontal Reach	3.00m
Up and Over Height	7.89m
Overall Length A	2.53m
Overall Width B	1.00m
Overall Height C	1.99m
Platform Size(Length/Width)	0.62m×0.87m
Ground Clearance(Stowed)	0.06m
Ground Clearance(Raised)	0.019m
Wheelbase D	1.22m
Turning Radius(Inside/Outside)	0.23/1.65m
Turret Rotation	345°
Jib Movement	+70°/-60°
Drive Motor	24V/1.5kW
Lifting Motor	24V/3kW
Travel Speed(Stowed)	4.5km/h
Travel Speed(Raised)	0.5km/h
Up/Down Speed	70/50sec
Batteries	24V/240Ah
Integrated Charger	24V/30A
Gradeability	25%
Max. Working Slope	2.5°
Tyres	Φ381×127mm
Weight	2950kg

Standard Equipment

- Proportional Controls
- Automatic Pothole Protection
- Self-lock Gate On Platform
- Drivable At Full Height
- Charger Protection
- Non Marking Tyre
- 2WD
- Automatic Brake System
- Emergency Lowering System
- Flashing Beacon
- Emergency Stop Button
- Cylinder Holding Valve
- Onboard Diagnostic System
- Tilt Sensor With Alarm

- 345°Turret Rotation
- All Motion Alarm
- Horn
- Hour Meter
- Swing Out Components Cover
- Platform Horizontal Outreach
- Overload Sensor With Alarm

Options

- Platform Work Lights
- AC Power To Platform
- Airline To Platform

