MARKET LEADER BUILT TOUGH

ACCE55 EXPRESS

SEN010.30.EM.OF

S03-ACE | Oil-Free Electric

SPECIFICATIONS


Size	Metric	British
Max. Working Height 🗛	5.05m	16ft 7in
Max. Platform Height 🕒	3.05m	10ft
Overall Length 🕞	1.16m	3ft 10in
Overall Width D	0.77m	2ft 6in
Overall Height 🕒	1.60m	5ft 3in
Platform Size(Length×Width)	1.16m×0.6m	3ft 10in×2ft
Ground Clearance(Stowed/Raised)	0.06m/0.016m	2in/1in
Wheelbase F	0.95m	3ft 1in
Turning Radius(Inside/Outside)	0.45m/1.20m	1ft 6in/3ft 11in
Tyres	φ200×80mm	φ200×80mm

Performance		
S.W.L	230kg	507lb
Max. Occupants	1	1
Gradeability	25%	25%
Travel Speed(Stowed)	4.0km/h	2.5mph
Travel Speed(Raised)	0.4km/h	0.25km/h
Max. Working Slope	1.5°/3°	1.5°/3°
Up/Down Speed	20/20s	20/20s


Weight		
Overall Weight	600kg	1322lb

Power		
Battery	2×12V/55Ah	2×12V/55Ah
Charger	24V/15A	24V/15A
Driving Motor	2×24V/0.6kW	2×24V/0.6kW
Lifting Motor	24V/1.5kW	24V/1.5kW









L 13 14 33 Www.accessexpress.com.au

SA

WA

VIC

flin