

MARKET LEADER
BUILT TOUGH

ACCESS
EXPRESS®



(08) 6159 4600 | (08) 8112 3700 www.accessexpress.com.au

WA

SA



Self-propelled Aerial Stock Picker
PARAMETER

Model	ZDYT 3-3.0S	ZDYT 3-3.7S	ZDYT 3-4.5S
S.W.L	300kg	300kg	300kg
Max. Occupants	1	1	1
Max. Working Height A	5.00m	5.70m	6.50m
Max. Platform Height B	3.00m	3.70m	4.50m
Overall Length C	1.56m	1.56m	1.59m
Overall Width D	1.06m	1.06m	1.06m
Overall Height E	2.07m	2.42m	2.28m
Platform Size(Length×Width)	0.71m×0.80m	0.71m×0.80m	0.71m×0.80m
Ground Clearance	0.08m	0.08m	0.08m
Wheelbase	1.27m	1.27m	1.30m
Turning Radius	0	0	0
Drive Motor	2×24VDC/0.4kW	2×24VDC/0.4kW	2×24VDC/0.4kW
Lifting Motor	24V/2.2kW	24V/2.2kW	24V/2.2kW
Travel Speed(Stowed)	4.0km/h	4.0km/h	4.0km/h
Travel Speed(Raised)	0.8km/h	0.8km/h	0.8km/h
Up/Down Speed	18/17sec	22/19sec	20/17sec
Batteries	2×12V/105Ah	2×12V/105Ah	2×12V/105Ah
Integrated Charger	24V/30A	24V/30A	24V/30A
Gradeability	25%	25%	25%
Max. Working Slope	1.5°/2°	1.5°/2°	1.5°/2°
Tyres(Drive Motors)	Φ 230×80mm	Φ 230×80mm	Φ 230×80mm
Tyres(Front Wheels)	6in	6in	6in
Weight	690kg	720kg	840kg

Standard Equipment

Proportional Controls
 Self-lock Gate On Platform
 Drivable At Full Height
 Non Marking Tyre
 2WD
 Automatic Brake System
 Emergency Lowering System
 Emergency Stop Button
 Cylinder Holding Valve
 Onboard Diagnostic System
 Tilt Sensor With Alarm
 All Motion Alarm
 Horn
 Hour Meter
 Automatic Pothole Protection
 Charger Protection
 Flashing Beacon
 Overload Sensor With Alarm

Options

Platform Work Light
 Chassis Protect Cover

