



# Self-Propelled Telescopic Booms

## SX-150

### Features

#### Standard Features

##### Measurements

- 48.33 m (158 ft) working height
- 24.38 m (80 ft) horizontal reach
- 340 kg (750 lb) lift capacity

##### Productivity

- Xchassis™ extendable axles
- 3.05 m (10 ft) 60° rotating jib
- Self-leveling platform
- 160° hydraulic platform rotation
- Proportional joystick controls
- Hydraulic oil cooler
- Drive enable
- AC power in the platform
- Horn
- Hour meter
- Tilt alarm
- Descent alarm
- 360° continuous turntable rotation
- Positive traction 4WD
- Two speed wheel motors
- Four wheel high angle steer
- Four steering modes: front, rear, crab and coordinated
- On board full diagnostics and engine monitoring display
- Dual flashing eacons
- Thumb rocker steer
- Entry toe boards
- Lockable platform control box cover
- Anemometer
- Telematics ready connector

##### Power

- 7.5 kW generator - 240V/50 Hz
- 12 V DC auxiliary power
- Auto engine fault protection
- Swing out engine tray

##### Engine Options

- Deutz turbo diesel 74 hp (55 kW)

##### Drive/Steer

- 4WD (standard)
- 4WS (standard)

##### Tyres

- Rough terrain foam-filled (standard)

#### Options & Accessories

##### Productivity Options

- Half-mesh platform inserts with swing gate
- Air line to platform
- Biodegradable hydraulic oil
- Hostile environment kit
- Deluxe hostile environment kit
- Light package
- Operator Protective Structure
- Operator Protective Alarm

##### Power Options

- Cold weather kit
- Diesel catalytic purifier muffler
- Diesel scrubber/catalytic muffler
- Intake air pre-cleaner

