

**MARKET LEADER
BUILT TOUGH**

**ACCESS
EXPRESS®**

JLG® COMPACT CRAWLERS



JLG
reachingout™

☎ 13 14 33

www.accessexpress.com.au

SA

WA

VIC



**MARKET LEADER
BUILT TOUGH**

**ACCESS
EXPRESS®**

JLG® Compact Crawler Series

REACHING OUT

Introducing the range of compact crawler boom lifts from JLG, specialists in off-slab and uneven terrain.

The JLG X-Series compact crawler boom lifts feature tracked wheel carriages that climb steps and a narrow chassis for access through gates, yards and doorways. Working heights range from 14m to 26m – platform capacities come with a dual-rated 120kg/200kg, or standard 230kg on the Plus models.

JLG Compact Crawlers are low weight and can be operated via an engine as well as electrically. This makes them extremely versatile, whether working indoors or out.

**YOUR MOBILE, LOW WEIGHT
TOOL FOR OVERHEAD WORK**



2

13 14 33

www.accessexpress.com.au

SA

WA

VIC



**MARKET LEADER
BUILT TOUGH**

**ACCESS
EXPRESS®**

JLG® Compact Crawler
X-series

JLG® Compact Crawler
X-series

SPECIALIST DESIGN

Whatever the task, JLG X-Series excel at multi-purpose application. JLG X-Series can go almost anywhere, the near square outrigger pattern helps provide additional stability, whilst the standard removable outrigger pads help minimize the impact to sensitive areas. The crawler carriage gives the X-Series its terrain ability, allowing it to climb grades up to 40%.

SPECIALIST DESIGN:

- Standard removable outrigger pads
- Extendable undercarriage
- Operating slope max. 11° (X23J up to 13°)
- Flexible positioning of outriggers (X23J)

TYPICAL AREAS OF APPLICATION:

- Gardening and landscaping
- Cleaning and maintenance
- Light construction
- Inspection and renovation work

EXCEPTIONAL FLEXIBILITY

The JLG X-Series are equipped as standard with an electric motor, an ideal solution when working indoor – as no noise or emissions are created. The engine (choice petrol or diesel) is mounted at the rear, as far away from the operator as possible. Optional 'zero maintenance' lithium batteries are available.

Three models from the JLG X-Series – the X17J Plus, the X20J Plus and the X26J Plus – allow for 230kg platform capacity, increasing productivity by permitting to bring additional tools into the basket, without restricting the work envelope.



Gradeability

Operating slope max. 11° (X23J up to 13°).



Specialist Design

Standard removable outrigger pads and basket. Extendable undercarriage provides additional stability during transport.



Flexibility

Several engine options available. All crawlers are equipped as standard with AC electric motor (110V/220V). Optional lithium batteries available.



Model Range

5 models with dual 120kg/200kg platform capacity 3 Plus models available with 230kg platform capacity working heights range from 14m to 26m.

13 14 33

www.accessexpress.com.au

SA

WA

VIC

f in

JLG® Compact Crawler
X-series

JLG® Compact Crawler
Specifications

GREATER ACCESSIBILITY

JLG X-Series compact crawler boom lifts deliver improved access in a multitude of ways. A narrow base and a low ground bearing pressure allow for travel on sensitive or uneven ground, and give access to areas where conventional machines are excluded because of physical size. All models are equipped with a remote drive control function and can be operated from the basket as well as remotely during transport when manoeuvring through confined space or loading/offloading. Thanks to the auto-leveling function, setting or retracting the outriggers is done automatically with ease.



GREATER ACCESSIBILITY:

- Low ground bearing pressure provides access to sensitive areas
- Narrow base allows for access to confined spaces
- Non-continuous swing of 361° for additional flexibility in positioning the product
- Optional non-marking tracks available

X-Series Compact Crawler Boom Lifts	X14J	X17J	X19J	X23J
Dimensions				
Working Height w 120 kg capacity	13.80 m	16.81 m	18.67 m	23.10 m
Working Height w 200 kg capacity	12.15 m	15.12 m	16.96 m	21.70 m
Horizontal Outreach (Std Platform w 120kg)	6.26 m	7.68 m	5.90 m	11.18 m
Horizontal Outreach (Std Platform w 200kg)	5.42 m	6.45 m	4.30 m	9.75 m
Platform size (standard 2 persons)	0.69 m x 1.30 m	0.76 m x 1.30 m	0.69 m x 1.30 m	0.69 m x 1.30 m
Stowed width (without platform)	0.79 m	0.79 m	0.79 m	0.99 m
Stowed height (on tracks)	2.07 m	1.99 m	1.98 m	1.99 m
Stowed length (on tracks)	4.02 m	4.53 m	4.47 m	6 m
Outrigger footprint	2.87 m x 2.91 m	2.89 m x 2.88 m	2.89 m x 2.88 m	3.98 m x 3.98 m
Machine weight (with standard platform)	1,998 kg	2,100 kg	2,080 kg	2,990 kg
Operating weight (with petrol engine)	1,430 kg	2,152 kg	2,106 kg	3,100 kg
AC electric motor	110V or 220V, 50Hz, 2.2KW	110V or 220V, 50Hz, 2.2KW	110V or 220V, 50Hz, 2.2KW	110V or 220V, 50Hz, 2.2KW
Engine	Honda GX270, 6.6 kw Petrol	Honda GX440, 11 kw Petrol	Honda GX440, 11 kw Petrol	Honda GX440, 11 kw Petrol

MAIN FEATURES

- Compact dimensions and low weight
- Low ground bearing pressure
- 361° non-continuous swing
- Load sensing under the Platform
- Standard auto-stabilisation
- Working indoor and out

X-Series Compact Crawler Boom Lifts	X17J Plus	X20J Plus	X26J Plus
Dimensions			
Working Height 230kg capacity	16.96 m	20.05 m	25.70 m
Horizontal Outreach (Std Platform 230kg)	7.00 m	9.20 m	13.20 m
Platform size (standard 2 persons)	0.69 m x 1.34 m	0.69 m x 1.34 m	0.69 m x 1.34 m
Stowed width (without platform)	0.795 m	0.795 m	0.990 m
Stowed height (on tracks)	2.00 m	1.99 m	1.98 m
Stowed length (on tracks, without platform)	4.53 m	5.00 m	5.98 m
Outrigger footprint	2.89 x 2.88 m	2.92 m x 2.93 m	4.08 m x 3.99 m
Machine weight (with standard platform)	2,190 kg	2,840 kg	4,365 kg
Operating weight (with petrol engine)	2,230 kg	2,880 kg	2,880 kg
AC electric motor	2.2 KW 50Hz 230V	2.2 KW 50Hz 230V	2.2 KW 50Hz 230V
Engine	Honda GX440, 11 kw Petrol	Honda GX440, 11 kw Petrol	Kubota D902-E3B

ON PLUS MODELS

- Forklift pockets
- Anchor points on outriggers
- 230 kg unrestricted platform capacity