MARKET LEADER BUILT TOUGH



10MSP MOBILE STOCK PICKER



Performance

Platform Height	10 ft	3.05 m
Working Height	16 ft	4.88 m
Drive Height	Max. Platform Height	
Stowed Height	57 in.	145 cm
Platform Entry Height	13.75 in.	35 cm
Platform Size (W x L)	20 x 27 in.	49.5 x 69 cm
Overall Vehicle Length		
Chassis Length	61 in.	155 cm
Overall Vehicle Width		
Chassis Width	32.5 in.	83 cm
Chassis Width (without bumper)	29.5 in.	75 cm
Gross Vehicle Weight	1,100 lb	499 kg
Capacity		
Platform	350 lb	159 kg
Carry Deck	250 lb	113 kg
Material Tray	250 lb	113 kg
Max. Drive Speed		
Platform Lowered	5.0 mph	8.0 km/h
Platform Elevated	0.5 mph	0.8 km/h
Turning Radius	Zero	
Gradeability	15%	
Underclearance	2 in.	5 cm

Standard Specifications

Power Source

Batteries	4 Sealed 210 amp-hr Maintenance Free (AGM)	
Battery Charger	25 Amp Automatic	
Drive System	4 Brush Direct Electric (planetary gear)	
Tires		
Rear Drive & Steer Wheels	12.62 x 4 in.	32 x 10 cm
Non-Marking Front Caster Wheels	8 x 2.5 in.	20 x 6 cm



Standard Features

- Heavy Duty Planetary Gear Drive Motors
- Simultaneous Lift and Drive Capability
- Point & Go[®] One-Hand
- Drive and Steer System
- Proportional Drive
- Automatic Five-Hour Battery Charger
- Battery Discharge Indicators —
- Platform and Base
- Lubrication-Free Anodized Aluminum
- Mast Sections
- Maintenance-Free Mast Guide System
- Strobe Lights Front and Rear
- Programmable Motion Alarm
- Slope Cut-Out Control Interlock

Accessories & Options

- Charger Cord Retractor
- Programmable 4-Digit Security Lock
- Guide Roller System
- Remote Manual Descent
- Object Sensing Pad

• Transportation Tie Downs

• ANSI, OSHA & CSA Compliant

Side and Front Bumpers

Electrically-Powered Material Tray

• Stand-On Foot Switch Operation

• Platform Gate Operation Interlock

• Lanyard Attachment Anchor Point

Adjustable Height Material TrayNon-Marking Tire Material

Enable Control

• Hourmeter

• Shipping Skid

• Horn

(200lb Capacity) • Rubber Floor Mat

L 13 14 33 www.accessexpress.com.au

SA

WA



flin