

AM SERIES

PUSH-AROUND VERTICAL LIFTS



Performance

| | | |
|---|---------------|------------|
| Working Height | | |
| 25AM | 31' | 9.45 m |
| 30AM | 35.7' | 10.88 m |
| 38AM | 44' | 13.4 m |
| Platform Height | | |
| 25AM | 24'10" | 7.57 m |
| 30AM | 29.7' | 9.05 m |
| 38AM | 38' | 11.58 m |
| Platform Capacity | | |
| 25AM | 350 lb | 160 kg |
| 30AM/38AM | 300 lb | 136 kg |
| Platform Size W x L | | |
| 25AM/30AM/38AM | 29.5" x 25.5" | |
| Overall Height | | |
| 25AM/30AM | 78" | 1.98 m |
| 38AM | 103.9" | 2.64 m |
| Overall Vehicle Width | | |
| 25AM | 29.5" | .75 m |
| 30AM/38AM | 29.1" | .74 m |
| Overall Vehicle Length | | |
| 25AM | 48" | 1.22 m |
| 30AM | 51.9" | 1.31 m |
| 38AM | 57.4" | 1.46 m |
| Overall Vehicle Length Without Battery Pack | | |
| 25AM/30AM/38AM | 47" | 1.19 m |
| Overall Height - Tilted Back | | |
| 25AM/30AM | n/a | |
| 38AM | 77.5" | 1.97 m |
| Overall Length - Tilted Back | | |
| 25AM/30AM | n/a | |
| 38AM | 119" | 3.02 m |
| Ground Entry Height | | |
| 25AM/30AM/38AM | 18.9" | .48 m |
| Outrigger Footprint Length | | |
| 25AM | 68.1" | 1.57 m |
| 30AM | 79" | 2.00 m |
| 38AM | 85.8" | 2.13 m |
| Outrigger Footprint Width | | |
| 25AM | 61.8" | 1.38 m |
| 30AM | 79" | 2.00 m |
| 38AM | 83.3" | 2.02 m |
| Distance to Wall - Front | | |
| 25AM | 6" | 15.5 cm |
| 30AM | 9.5" | 24.13 cm |
| 38AM | 15" | 38.1 cm |
| Distance to Wall - Side | | |
| 25AM | 11.5" | 28.9 cm |
| 30AM | 20.5" | 52.07 cm |
| 38AM | 24" | 61 cm |
| Weight | | |
| 25AM - AC/DC | 825/905 lb | 374/411 kg |
| 30AM - AC/DC | 1030/1110 lb | 467/503 kg |
| 38AM - AC/DC | 1265/1395 lb | 574/633 kg |



Standard Specifications

Wheels

| | | |
|---------------------|------------|---------------|
| Rear Drive Wheels | 10 x 2 in. | 25.4 x 5.1 cm |
| Front Caster Wheels | 6 x 2 in. | 15.2 x 5.1 cm |

Standard Features

- Lanyard Attachment Anchor for Body Harness
- Quick-Change 26 in. W x 28 in. L (.66 x .71 m) —Gull-Wing Entry Platform
- Quick-Change Platform Mounts
- Low Maintenance Anodized Mast
- Non-Marking Tires
- 110 Volt Double Receptacle in Platform
- 93 AH Lead-Acid Battery—DC Models Only
- Descent Alarm
- Automatic Battery Charger—DC Models Only
- Battery Discharge Indicator (BDI)
- Hourmeter
- Roller Loading Device: For Loading on Pickup Trucks
- Auto Power Saver—Shuts Off Power When Idled
- ANSI, OSHA & CSA Compliant

Accessories & Options

- 22x22" Gullwing Platform
- 26x26" Ride Side Entry Platform
- Tool Tray
- 8 x 18 x 5 (20 x 46 x 13 cm)
- Programmable 4-Digit Security Lock
- Crane Hook
- Locking Casters
- Auxiliary Lowering