

AM SERIES

PUSH-AROUND VERTICAL LIFTS



Performance

Working Height		
25AM	31'	9.45 m
30AM	35.7'	10.88 m
38AM	44'	13.4 m
Platform Height		
25AM	24'10"	7.57 m
30AM	29.7'	9.05 m
38AM	38'	11.58 m
Platform Capacity		
25AM	350 lb	160 kg
30AM/38AM	300 lb	136 kg
Platform Size W x L		
25AM/30AM/38AM	29.5" x 25.5"	
Overall Height		
25AM/30AM	78"	1.98 m
38AM	103.9"	2.64 m
Overall Vehicle Width		
25AM	29.5"	.75 m
30AM/38AM	29.1"	.74 m
Overall Vehicle Length		
25AM	48"	1.22 m
30AM	51.9"	1.31 m
38AM	57.4"	1.46 m
Overall Vehicle Length Without Battery Pack		
25AM/30AM/38AM	47"	1.19 m
Overall Height - Tilted Back		
25AM/30AM	n/a	
38AM	77.5"	1.97 m
Overall Length - Tilted Back		
25AM/30AM	n/a	
38AM	119"	3.02 m
Ground Entry Height		
25AM/30AM/38AM	18.9"	.48 m
Outrigger Footprint Length		
25AM	68.1"	1.57 m
30AM	79"	2.00 m
38AM	85.8"	2.13 m
Outrigger Footprint Width		
25AM	61.8"	1.38 m
30AM	79"	2.00 m
38AM	83.3"	2.02 m
Distance to Wall - Front		
25AM	6"	15.5 cm
30AM	9.5"	24.13 cm
38AM	15"	38.1 cm
Distance to Wall - Side		
25AM	11.5"	28.9 cm
30AM	20.5"	52.07 cm
38AM	24"	61 cm
Weight		
25AM - AC/DC	825/905 lb	374/411 kg
30AM - AC/DC	1030/1110 lb	467/503 kg
38AM - AC/DC	1265/1395 lb	574/633 kg



Standard Specifications

Wheels

Rear Drive Wheels	10 x 2 in.	25.4 x 5.1 cm
Front Caster Wheels	6 x 2 in.	15.2 x 5.1 cm

Standard Features

- Lanyard Attachment Anchor for Body Harness
- Quick-Change 26 in. W x 28 in. L (.66 x .71 m) —Gull-Wing Entry Platform
- Quick-Change Platform Mounts
- Low Maintenance Anodized Mast
- Non-Marking Tires
- 110 Volt Double Receptacle in Platform
- 93 AH Lead-Acid Battery—DC Models Only
- Descent Alarm
- Automatic Battery Charger—DC Models Only
- Battery Discharge Indicator (BDI)
- Hourmeter
- Roller Loading Device: For Loading on Pickup Trucks
- Auto Power Saver—Shuts Off Power When Idled
- ANSI, OSHA & CSA Compliant

Accessories & Options

- 22x22" Gullwing Platform
- 26x26" Ride Side Entry Platform
- Tool Tray
- 8 x 18 x 5 (20 x 46 x 13 cm)
- Programmable 4-Digit Security Lock
- Crane Hook
- Locking Casters
- Auxiliary Lowering