

JCPT0807AC SCISSOR LIFT**DINGLI®**

19FT ELECTRIC SCISSOR LIFT NARROW ELECTRIC MOTOR DRIVE

Size	Metric	British
Max. Working Height A	7.80m	25ft 7in
Max. Platform Height B	5.80m	19ft
Overall Length C	1.86m	6ft 1in
Overall Width D	0.76m	2ft 6in
Overall Height(Rails Up) E	2.15m	7ft 1in
Overall Height(Rails Down) F	1.83m	6ft
Platform Size(Length×Width)	1.67m×0.74m	5ft 6in×2ft 5in
Platform Extension Size G	0.90m	2ft 11in
Ground Clearance(Stowed/Raised)	0.09m/0.016m	4in/1in
Wheelbase H	1.36m	4ft 6in
Turning Radius(Inside/Outside)	0m/1.64m	0in/5ft 5in
Tyres	Φ323×100mm	Φ323×100mm

Performance

S.W.L	230kg	507lb
S.W.L On Extension	113kg	249lb
Max. Occupants	2	2
Gradeability	25%	25%
Travel Speed(Stowed)	4.5km/h	2.80mph
Travel Speed(Raised)	0.6km/h	0.37mph
Max. Working Slope	X-1.5°/Y-3°	X-1.5°/Y-3°
Up/Down Speed	21/25sec	21/25sec

Weight

Overall Weight(Lead-acid Battery)	1630kg	3593lb
Overall Weight(Lithium Battery)	1580kg	3483lb

Power

Hydraulic Tank	6.5L	1.7gal
Battery	24V/185Ah	24V/185Ah
Charger	24V/30A	24V/30A
Driving Motor	2×24VAC/0.5kW	2×24VAC/0.5kW
Lifting Motor	24VAC/3.0kW	24VAC/3.0kW

